



PHARMA MACHINERIES



RIDDHI PRESS MARK IV



RIDDHI PRESS MARK IV

1. It is a high speed Rotary tablet press for higher table output, suitable for large batch production.
2. Machine is having a square design with full consideration of GMP standards.
3. All the tablet parameters can be fine tuned during the operation of the machine from front side which are at outside the machine, having SEIKO type dials.
4. The machine is having elegantly designed cabinet top of SS-304.
5. The machine is having round hoppers of SS-304 with Butterfly valve.
6. The machine is having Pre-compression feature.
7. The machine is equipped with A.C. variable frequency drive for the main motor.
8. Machine is also having A.C. variable frequency drive for force feeding motors, which enables operators to synchronize machine's speed & feed both.
9. The machine is having Electromagnetic clutch arrangements.
10. The machine is having one piece turret of special grade casting. However, three piece turret with SS-304/SS-316 middle plate is also available (optionally). Electro less nickel plating can also be available to the turret (optionally).
11. Lower punch seals are provided at lower punch hole in turret (optionally).
12. The machine is having Helical gear ring to drive the turret.
13. The machine is having hard chrome plated, MS Fabricated upper roll carriers.
14. The machine is having BALL BEARING TYPE upper & lower pressure rolls.
15. The machine is having specially designed pressure Link Assly. which ensures sufficient & equal pressure to the tablets.
16. The machine is having tablet weight consistency.
17. The machine is having sturdy Aluminium section framed, Polycarbonate guards with SS Hinges & Handle & are also fitted with Gas Filled – Sock absorbers.
18. The lower guard of the machine are of SS-304 material having excellent matt finish.
19. All guards are interlocked for safety.
20. The machine is having auto lubrication system.



RIDDHI PRESS MARK IV

21. There is no colour part in tablet manufacturing zone & all other parts are either of SS-304 material or Gunmetal or of hard chrome plated. All Hardware are used of SS-304 quality in tablet manufacturing zone.
22. The machine is having box type Detachable control panel having all electrical controls on the top. Acrylic cover is also provided to protect the controls from the dust.
23. The machine is having center Drive Type Gear Box.
24. The machine is having Hydraulic Power pack for pressure loading and overload release.
25. A Hydraulic Gauge is also provided on lower guard for easy view.
26. The machine is having anti vibrating mounts.
27. The machine is having excellent bottom driven force feeding system for material feeding. However, Gravity type feeding also can be provided optionally.
28. Two layer attachment can also be provided, optionally.
29. The machine is having excellent paint, inside wherever it is required.
30. The machine has been designed as to minimize the change over time. The weight adjustment section is easily removable which provides good access for the removal/replacement of lower punches & dies, away from compression zone.
31. The hand wheel is conveniently located for indexing the turret during tooling change over with single operator.
32. The machine is having specially designed Dust Extractor Nozzle which can be connected with the dust Extractor, away from machine.
33. The machine is having Elegant Look & operator friendly design and is manufactured in such a manner that it gives all satisfaction to the operator while the production. The machine are backed by excellent after self service.



Model No.	PRESS-IV-45	PRESS-IV-55	PRESS-IV-69	PRESS-IV-75
No. of Stations	45	55	69	75
Type of Tooling	D	B	BB	BB
Output – Tablets/Hr.(Max./Min)	3,25,000 TO 65,000	3,96,000 TO 79,000	4,97,000 TO 99,000	5,40,000 TO 1,08,000
Max. Operating Pressure	100 kN	65 kN	65 kN	65 kN
Max. Operating Pressure (Pre-Compression)	10 kN	10 kN	10 kN	10 kN
Max. Tablet Dia.	25 mm	16 mm	11.1 mm	11.1 mm
Depth of fill	20 mm	17.4 mm	17.4 mm	17.4 mm
Upper Punch entry	2 to 8 mm	2 to 8 mm	2 to 8 mm	2 to 8 mm
Power Total	8.75 kW/11.7 HP	8.75 kW/11.7 HP	8.75 kW/11.7 HP	8.75 kW/11.7 HP
Main Electric Motor	7.5 kW / 10 HP	7.5 kW / 10 HP	7.5 kW / 10 HP	7.5 kW / 10 HP
Force Feeder Motor	0.19 KW / 0.25 HP	0.19 kW / 0.25 HP	0.19 kW / 0.25 HP	0.19 kW / 0.25 HP
Overall Dimension s	68" x 64" x 76" (H) – Approx.			
Net Weight (Approx)	3700 Kgs. – Approx.			

RIDDHI PHARMA MACHINERY LTD.

Manufacturer & Exporters of Pharmaceutical Machineries

MUMBAI OFFICE: Om-shivam soc., Tarun Bharat Bldg. No.2, Opp. Cigaratte Factory, Sahar Road, Andheri (East), Mumbai - 400 099. Maharashtra, India Tel.: +91-22-28321332 / 28382479 Mobile: +91- 9821018579

Skype : hiten.k.shah **Whatsapp :** 9821018579 / 9969994187 **Email:** hkshah@riddhipharma.com

Web : www.riddhipharma.com / www.riddhipharma.net

REGD. OFFICE & FACTORY : Riddhi Estate, Gulab Nagar, Opp. AEC, Amraiwadi, Ahmedabad - 380026. India.