

PHARMA MACHINERIES



MULTI MILL - GMP MODEL











MULTI MILL - GMP MODEL

APPLICATIONS: Multi Mill is widely used for wet and dry granulation, pulverisation etc. in Pharmaceuticals, Chemicals, Cosmetics, Ceramics, Colours, Dyestuff, Food products etc. It also finds application in Pesticides, Fertilizers, Spices, Detergents, Insecticides, Plastic and Resins Industries.

DESCRIPTION: Unit consists of S.S. 304 quality hopper and processing chamber (can be provided is S.S. 316 quality at extra cost) withbeaters assembly, motor, reversible switch, DOL starter, fourspeed step pulley, Suitable screen with painted pillar mountedon base plate, with castors.

OPERATION: It operates on the principle of variable force swing beatershaving both knife and impact edges rotating within aselected screen to get the required size reduction. Material fed in the hopper, goes down to the processing chamber where it moves to the periphery and passesthrough the screen radially and tangentially. Finally the processed material gets collected in the container keptbelow the processing chamber. Output and quality of the final product depends on threemain factors: (1) Shape of beaters (knife/impact edges),

(2) Speed and (3) Screen.

SALIENT FEATURES: Direction of beaters can be changed by reversible switch fromknife to impact forward and vice-versa. All contact parts can be easily and quickly dismantled and cleaned. Machine is designed for continuous operation. Cylindrical screen for higher output. Castors provided for mobility. Flame proof electricals can be provided at extra cost. Beaters and scrapper blades of SS 410 quality are hardened and hard chrome plated.



• TECHNICAL SPECIFICATIONS:

<u>PARAMETER</u>	<u>SPECIFICATIONS</u>
Model No.	RDMM – MINI
Type	GMP – Contact Parts S.S. 316
Output	10 Kg./Hr. Depending upon product & Sieve Size.
Overall Dimensions	550 x 400 x 950(H) – in mm. Approx.
Motor RPM	2800
Rotor Assembly Dia./ Swing Dia.	155mm
Rotor Speed	750 / 1500 / 3000 RPM
Shape of Beater	Knife / Impact Edge & Swing Type
Size & No. of Beaters	70mm Long & 6+ 2 = 8 Nos. of Beaters
Screen Dimensions	OD-165 x 82mm Height – Approx.
Model	GMP
MOC – Contact Parts	S.S.316
FLP Motor	0.5 HP / 2800 RPM / 415v / 3Ф AC Supply Non FLP
FLP Starter	0.5 HP Non FLP Starter
Power Requirement	415V / 3 Ф A.C. Supply
Material Charging Height	840mm Approx.
Material Discharging Height	350mm Approx.
Net Weight	110 Kgs. Approx.
Floor Dimensions	800 x 750 x 1500(H) – in mm. Approx.

RIDDHI PHARMA MACHINERY LTD.

Manufacturer & Exporters of Pharmaceutical Machineries

OFFICE: MUMBAI Om-Shivam Bldg.,2, Tarun Bharat, Sahar Rd, Andheri(E), Mumbai-400 099.Maharashtra, India. Tel.: 91-22-2832 1332 / 2838 9432 Fax: 91-22-2838 2479 Res: 91-22-2683 3777, Mob: 98210 18579 Whatsapp: 919821018579 Skype: hiten.k.shah

E-mail: hitenkshah@hotmail.com/ hitenks@vsnl.com **Website:** www.riddhipharma.com **FACTORY:** Riddhi Estate, Gulab Nagar, Opp. AEC, Amraiwadi, Ahemdabad-380 026. India.